R. C. Tronics Incorporated

2573 East Kercher Road Goshen, Indiana 46528 Toll Free 1-866-457-7790

DAT-01348-01006

Phone 1-574-642-3857
Fax 1-574-642-3858

08 Conductor Data Cable http://www.rctronics.com

Viewed with Tyco Connector Plug-In Face Down.



Operates Relays 7A & 7B on RCT-00786 or RCT-01414, Bus Power Center from J3 on RCT-00948, with "IGNITION", Dash Switch Center.

Operates Aux. 3 & Mirror with "IGNITION", on RCT-01490 / RCT-01507 from J3 on RCT-01492 / RCT-01493.

Carol C-2465, 22 AWG, Stranded 7/30/8, unshielded eight conductor cable.

Cut each jacket end 4 inches long, remove jacket on each end.

Requires one (1) Tyco/Amp. 643814-8 connector & Tyco/Amp. 643075-8 end cap.

Terminate One End Only.

Place connector into insertion equipment, start with #8 and complete with #1

Wire Nut; Black, Red, and White together.

#1 BLACK, #2 RED, #3 GREEN, #4 BROWN,

#5 BLUE, #6, ORANGE, #7 YELLOW, #8 WHITE

D A	1st three Letters = Data Cable
T	
0 0 0 0	2nd five numbers = Print Number
0	3rd two numbers = Configuration
0	4th two numbers = Length In Feet
0	5th last digit = Length In Inches