R. C. Tronics Incorporated

2573 East Kercher Road Goshen, Indiana 46528 Toll Free 1-866-457-7790

WIRE NUT TOGETHER

DAT-01348-15013

Phone 1-574-642-3857
Fax 1-574-642-3858
http://www.retronics.com

08 Conductor Data Cable http://www.rctronics.com

Viewed with Tyco Connector Plug-In Face Down. DAT-01348-15013 (15 INCH) 08 Red Yellow Orana White Blue Brown TAPE Blue Green Battery & Low Voltage Light TAPE Brown Red Yellow Requires .250 Female Tab. Black Orange

Connects to PCB-00745/J1 from PCB-00747.

Operates; "Emergency Master Light, Door Open Light and Compartment Open Light."

Yellow and Orange wires Inhibit, "Low Voltage Alarm."

Carol C-2465, 22 AWG, Stranded 7/30/8, unshielded eight conductor cable.

Cut each jacket end 6 inches long, remove jacket on each end.

Place connector into insertion equipment, start with #8 and complete with #1

Requires one (1) Tyco/Amp. 643813-8 connector & Tyco/Amp. 643075-8 end cap.

Terminate right end as shown.

Requires one (1) Tyco/Amp 643813-4 & Tyco/Amp. 643075-4 end cap.

Terminate left end as shown.

CHECK CABLE WITH CABLE CHECKER

#1 BLACK, #2 RED, #3 GREEN, #4 BROWN,

#5 BLUE, #6, ORANGE, #7 YELLOW, #8 WHITE

D Α 1st three Letters = Data Cable Τ 0 0 0 2nd five numbers = Print Number 0 0 0 3rd two numbers = Configuration 0 0 4th two numbers = Length In Feet 0 0 5th last digit = Length In Inches